





Powerful and reliable solution for cleaning of dust, liquid and solid material

Roots -Perfect from product to service



## **FILTRATION**

The DG 30/70 machines are provided with a filter surface up to 30,000 cm $^2$  and air load on filter (m $^3$ /m $^2$ /h) according to BIA standards to maximize the efficiency, vacuum performance and lifetime of the machine.

Absolute filters (99.995% DOP efficiency) are provided for filtering toxic dust.

## **POWER**

The DG 30/70 machines are provided with side channel blower from the world's best manufacturers, to improve the quality and performance. They are powerful, silent and suitable for continuous and heavy works. They don't require maintenance and they don't wear since there is no transmission system.



The DG 30/70 machines are designed to draw in dust, liquids and solids at the same time. The releasable wheeled container aids in easy emptying of the collected material. The external filter shaker keeps the vacuum performance and the filtration efficiency maximum during operation.









TECHNICAL DATA	UNITS	DG 30	DG 70
Voltage	Volts/Hz	415/50	415/50
Power	kW/HP	2.2/3	5.5/7.5
Max. Vacuum Rate*	mm.H₂O	3000	3500
Max. Airflow Rate**	m³/h	300	600
Type of Filter	Pocket	Polyester	Polyester
Filter Efficiency	Micron	3	3
Filter surface (pocket filter)	cm²	20,000	30,000
Filter surface (cartridge filter) Optional	cm²	26,500	52,500
	H14 with 99.995% efficiency at 0.18μm particles		
Capacity	L	100	100
Suction Inlet Dia	mm	80	80
Noise Level	dB(A)	72	74
Protection	IP	55	55
Insulation	Class	F	F
Dimensions	mm.	640 x1144 x 1540	655 x1215 x 1558
Weight	kg	120	165

<sup>\*</sup>Measured with fully closed suction inlet \*\* Measured with fully open suction inlet



Roots Multiclean Ltd.

R.K.G. Industrial Estate, Ganapathy, Coimbatore - 641 006. India.

Tel: +91 422 4330 330 | Email: rmclsales@rootsemail.com | Customer care: 95978 12345

Website: https://www.rootsmulticlean.com